

## PRODUCT FEATURES

- 1. Fitted with the all new Tier 3 Emmisions diesel engine. Elecronically controlled for better fuel economy and reliability.
- 2. Shift 12F+12R, forward reverse shuttle, gear levers to the right side for ease of operation.
- 3. Rear 3 point linkage has down force as a standard feature.
- 2. The new dash design is easy to read, also fitted is a full lighting system.
- 5. Ratomolding fuel tank with easy access for filling.
- 6. Adopting the car paint technology for all cover parts.
- 7. High quality oil seals and bearings are used throughout the tractors, giving more relaiblity for longer.
- 8. All of the weldments use spray plastic technology, better anti-corrossion effect.



The new combination instrument



Right side centralized control



Environmentally and fuel-efficient



Suitable for all kinds of working environment



## **FMD B-Series Wheeled Tractors**

## TECHNICAL SPECIFICATION

MODEL	FMD-404
Type Drive Type	2WD/4WD
	2000/4000
Engine  Engine model Engine Type Emmissions type Fuel type No of cylinders Powers figures Control system	YD4J45V2 Naturally aspirated Tier 3 Elecronic controlled Diesel 4 Cylinder 34 KW / 40 HP @2300 RPM ECU
Transmission	
Clutch Type Gearbox Gear lever postion Speed in high	Dual stage 11 Inch Dry 12F/12R Shuttle Side 30KPH
Hydraulics	
Hydraulic drice type Hydraulic LPM	Gear drive 40 LPM (320 pump)
Working device	
Three-point linkage PTO speed Hydraulic down force	Cat 1 540/100 RPM Yes
Parameter	
Whole machine dimensions (mm)  Ground clearance Working weight W/O Loader(Kg) Tyre/rim size Tyre type Alr Cab	L. 2900mm with loader 4000mm H. 2750mm W. 1520 mm 340mm 2120kgs 8.3-20 / 12.4-28 R1 Style Ag tyre Optional

Wet disk type

Hydrostatic power steering

Seperate hand brake lever



Brake System Steering type Hand brake

Specs may change without notice.











